

Main dimensions and tolerance												Eccentricity μm	Squareness μm	Basic load rating		Weight g	Shaft diameter				
dr	D		L	Flange							dynamic C(kg)			static Co(kg)							
	Tolerance μm	Tolerance μm		Tolerance μm	Df	K	t	Dp	X	Y					Z						
6	0 -10	12	0 -13	35	0 -300	28	22	5	20	3.5	6	3.1	15	15	33	54	31 25	6			
8		15		45		32	25		24						6	4.5	7.5	4.1	44	80	51 43
10		19		55		40	30	29	8	5.5	9	5.1							60	112	98 78
12		21	57	42		32	32	10											6.6	11	6.1
13		23	61	43		34	33								13	9	14	8.1			
16		28	70	48		37	38		18	112	11	17									
20	32	80	54	42	43	25	25	770					2,040	4,500 4,060					143	280	260 225
25	40	112	62	50	51										30	30	770	2,040	4,500 4,060	159	320
30	45	123	74	58	60				35	35	770	2,040								4,500 4,060	254
35	52	135	82	64	67	40	40	770					2,040	4,500 4,060							270
40	60	151	96	75	78										50	50	770	2,040	4,500 4,060		350
50	80	192	116	92	98				60	60	770	2,040								4,500 4,060	620
60	90	209	134	106	112	60	60	770					2,040	4,500 4,060							770